












Installation Instructions
JLT True Cold Air Intake Kit for 2003-04 SVT Cobra
#CAI-FMC-0304

Thank you for purchasing our product. We hope you are satisfied with the look and performance. You may use any polish or wax on the pipe as it's painted with the same high quality paint as your car. It is also recommended to use some tire shine on the rubber elbow. Please note, with such a large pipe the fit is tight. Take your time and it will be a smooth install.

Please review complete instructions prior to installing.

Step#	
1	<p>Verify you have all of the following parts included in the kit: (1) JLT painted pipe with Vacuum fitting, PCV fitting and IAT grommet (1) 45° Rubber Elbow w/ clamps to connect throttle Body to JLT Pipe, (1) 90° Rubber Elbow w/clamps to connect JLT Pipe to MAF (1) Silicone Spacer to take up space between 90° Rubber Elbow and MAF, (1) Apron Plate with "U" Channel Gasket, (1) PCV hose & valve cover fitting, (1) Vacuum Line (1) Billet MAF Adaptor with bolts, (1) 4x6" S&B Air Filter</p>
2	<p>Gather all of the following tools needed for the installation: 5/16 Nut Driver, 10mm Open End Wrench, 11mm Open End Wrench, Phillips Head Screwdriver, Car Jack and Jack Stands</p>
3	<p>Jack the car up using jack stands or drive it on some ramps. Removing the right wheel makes the install much easier, but not totally necessary.</p>
4	<p>Remove your stock intake system from the throttle body to the filter housing.</p>
5	<p>Unbolt your Mass Air Flow Sensor from the filter housing, and install the MAF filter adaptor. Do not reuse the screen.</p> <div style="text-align: center;">  </div>
6	<p>Unplug the hold down in the large wire harness where the MAF wire ties into it and pull toward the hole. Feed your MAF wires into the hole in the apron. You only need a few inches in there.</p>
7	<p>Put some tape around the hole in the apron. This will help prevent scratching the pipe during install.</p> <div style="text-align: center;">  </div>

8	Remove your air temperature sensor from your stock inlet and install in the grommet on bottom side of JLT pipe.
9	Remove the large vacuum connection on the line at throttle body. 
10	Use the supplied "U" channel gasket and install around the hole in apron plate. 
11	Slide apron plate with "U" channel gasket and 90° rubber elbow onto pipe. Use soapy water on the elbow and leave it loose. You will need to move it for best fit in the fender well. 
12	Put a small amount of soapy water on the inside of 45 degree elbow and connect to pipe. Stand pipe up and "screw" it into the hole in the apron. Connect the new vacuum line to the original and plug in the air temp. before attaching to throttle body. 

<p>13</p>	<p>Twist elbow for best angle and fit. Leave clamps loose for now. Push and twist pipe and elbow for best fit. The elbow will be "just" touching the strut tower. Pipe may also "just" touch valve cover. If this concerns you, put a small piece of Velcro on the pipe or cover, soft side.</p>
<p>14</p>	<p>Screw 90 degree fitting supplied in the kit, into the grommet in your valve cover and using the ½" hose connect the valve cover fitting to the fitting on the bottom of the JLT pipe. This will connect your factory PCV.</p> 
<p>15</p>	<p>Now from underside of car, install Silicone Spacer on MAF.</p> 
<p>16</p>	<p>Remove the Phillips head screw from the bumper cover in front of right wheel. Pull back your splash shield, and feed the MAF adaptor and filter as a unit (we think this is the best way) into rubber elbow and clamp down. Position the MAF so the plug points at the driver's fender and the top points toward the rear of the car. Then tighten clamp. If that is too much, do it a piece at a time.</p>  <p>You may need to twist the pipe to get a better angle for the filter. It's tight but it will fit. If needed, loosen the upper clamp and adjust the angle of all the connections.</p>

17 Installation is complete. Go back and tighten all your clamps, polish your fingerprints off the paint and hit the track, street and/or dyno.



This kit includes an S&B Powerstack pre-oiled reusable air filter. The frequency you should clean your filter will depend on your driving conditions. S&B recommends checking your filter at every oil change or 3,000 miles. If there is a build up of dirt as thick as the wire mesh, then S&B recommends you clean your filter. As dirt builds up on your filter, the restriction of the airflow also increases. More frequent cleanings will improve your fuel economy and your vehicle's performance.

To properly clean your filter, we recommend the S&B Air Filter Revitalizer Kit (located on our website in the Parts Sold Separately Section). This is an easy and safe to use kit, which includes a filter cleaning solvent to release accumulated dirt, and a spray on fabric filter oil for maximum dirt filtration.

Thanks for the business. If you have any questions, please e-mail Jay@JLTtruecoldair.com or call 757-335-1940. Our hours are 8:00am – 5:00pm Eastern Time.

Warranty: JLT Performance Inc. will repair or replace any part of their product found upon our inspection to be defective in workmanship or material within 1 year from the purchase date for the original purchaser.

Disclaimer: JLT Performance Inc. makes no warranties whatsoever, expressed or implied, oral or written to any purchasers, except the warranty above. JLT Performance Inc. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by JLT Performance Inc. agree to hold harmless and indemnify JLT Performance Inc. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to JLT Performance Inc. for any claims arising out of use of its products.

Custom Paint Disclaimer: All custom paint jobs are done by JLT Performance Inc. Every job is different and done by hand. By ordering a custom paint job, you accept this fact and cannot hold JLT Performance liable for the end result not being exactly what you had in your mind.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Air Filters will not be accepted for return unless they are in original plastic sealed bag. Please visit www.JLTtruecoldair.com for complete return policy.